

RM-8WAY-24VAC RELAY MODULE



RM-8WAY-24VAC Relay Module

The relay module provides 8 relays, either mechanical Finder 46.61-024-DC relays or Autonics SRS1 solid state relays. The relay module can be populated with a mixture of mechanical relays or solid state relays to suit the loads being switched.

Relay control is via terminals using an external 24V AC or DC supply.

Order code:

RM-8WAY-24VAC 8 way relay module.


Fitted with Finder 46.61-024V-DC relays

Optional customer specified mixture of
Finder 46.61-024V-DC relays or
Autonics SRS1 solid state relays on request

Specifications

Outputs	8 relays with fuse holders * NOTE fuses not supplied with the unit Either Finder 46.61-024-DC mechanical relays or Autonics SRS1 solid state relays with NO outputs 46.61-024-DC relays : 250VAC 10A CO (fuse/fuse holder limited) SRS1-A1205 relays : 24-240VAC 5A NO SRS1-A1D102 relays : 5-100VDC 2A NO
Relay Control	: 8x 24V AC or DC via terminals : approx. 30mA per relay at 24Vac, 27mA per relay at 24Vdc : operating range 18V to 28V, AC or DC
Temperature	Operating : -10°C to +60°C Storage : -20°C to +70°C
EMC Compliance	: AS/NZS 61000.6.3:2012
Housing	DIN rail mounted polyamide, flame retardant UL 94 V0.
Terminals	Spring steel clamp, tin plated copper alloy terminal : up to 1.5mm ² stranded conductor : wire stripping 9mm

Relay Output Configuration Mechanical Relays or Solid State Relays




Note. No NC connection with solid state relays.

CARREL ELECTRADE LTD

MANUFACTURERS, IMPORTERS AND DISTRIBUTORS OF ELECTRICAL ENGINEERING PRODUCTS
POSTAL ADDRESS: P O BOX 11078, ELLERSLIE 1542, AUCKLAND NEW ZEALAND
FACTORY AND OFFICE: 661 GREAT SOUTH ROAD, PENROSE 1061
TELEPHONE: +64-9-525 1753 FACSIMILE: +64-9-525 1756
CHRISTCHURCH BRANCH: 73B BRISBANE STREET, SYDENHAM
TELEPHONE: 03-366 1242 FACSIMILE: 03-379 1991
EMAIL: sales@ carrel-electrade.co.nz WEB: www.carrel-electrade.co.nz

RM-8WAY-24VAC RELAY MODULE

Dimensions



Circuit Diagram

